


SKT	PART NO.	DIM. 1	DIM. 2	DIM. 3	DIM. 4	EDP NO.	VΔ=FORMED POST
3	91208-03	3.0	5.0	5.4	6.0	08072037	▽△▽
4	-04	4.5	6.5	6.9	7.5	038	▽△▽△
5	-05	6.0	8.0	8.4	9.0	039	▽△▽▽
6	-06	7.5	9.5	9.9	10.5	040	▽△▽▽▽
7	-07	9.0	11.0	11.4	12.0	041	▽△▽▽▽△
8	-08	10.5	12.5	12.9	13.5	042	▽△▽△▽▽
9	-09	12.0	14.0	14.4	15.0	043	▽△▽△▽▽▽
10	-10	13.5	15.5	15.9	16.5	044	▽△▽△▽△▽▽
11	-11	15.0	17.0	17.4	18.0	045	▽△▽△▽△▽△
12	-12	16.5	18.5	18.9	19.5	046	▽△▽△▽△▽△△
13	-13	18.0	20.0	20.4	21.0	047	▽△▽△▽△▽△▽
14	-14	19.5	21.5	21.9	22.5	048	▽△▽△▽△▽△▽△
15	-15	21.0	23.0	23.4	24.0	049	▽△▽△▽△▽△▽△△
16	-16	22.5	24.5	24.9	25.5	050	▽△▽△▽△▽△▽△△
17	-17	24.0	26.0	26.4	27.0	051	▽△▽△▽△▽△▽△△▽
18	-18	25.5	27.5	27.9	28.5	052	▽△▽△▽△▽△▽△△▽
19	-19	27.0	29.0	29.4	30.0	053	▽△▽△▽△▽△▽△△▽
20	91208-20	28.5	30.5	30.9	31.5	08072054	▽△▽△▽△▽△▽△△▽

NOTE

1. MAXIMUM RATING VOLTAGE AND CURRENT : 125V 1A(AC/DC)
2. TEMPERATURE RANGE : -55°C TO +105°C
3. GENERAL TOLERANCE : ±0.3
4. MATERIAL : 1. BASE : GLASS FILLED 66NYLON UL94V-0
 2. POST : BRASS(CDA 28000 3/4 HARD 0.48Q.)
 COLOR: IVORY
5. FINISH : PRE-PLATED
 COPPER UNDER PLATE 0.5μMIN.
 TIN-LEAD PLATE 0.8μMIN. (CONTAINED LEAD 100%)



NO. PARTS NO. DIM. 1 DIM. 2 DIM. 3 DIM. 4 PARTS NAME MATERIAL FINISH TITLE REMARKS
 DRAWN BY: [Signature] ENGINEER
 CHECKED BY: [Signature] APPROVED
 SCALE: PARTS NUMBER: 91208-11
 IRISO ELECTRONIC CO. LTD. TOWN NUMBER: [Blank]
 TOKYO, JAPAN. PHONE NUMBER: [Blank]