


極数	部品番号	A	B	NOTE
CKT	PARTS No.			
6	9201B-1-06Z248-PT1	12.70	15.20	
7	9201B-1-07Z248-PT1	15.24	17.74	
12	9201B-1-06Z248-PT1	27.94	30.44	

仕様

- 1. 最大定格電圧電流 : 250V, 3A (AC, DC)
- 2. 使用温度範囲 : -40~+105℃



NOTE

- 1. MAXIMUM RATING VOLTAGE AND CURRENT : 250V, 3A (AC, DC)
- 2. TEMPERATURE RANGE : -40~+105℃

△						MATERIAL 材質	GENERAL TOLERANCES 一般公差	SCALE 尺度	UNIT 単位	TITLE 名称
△						① ベース : ガラス入りPBT樹脂 黒色 UL94V-0	± 0.3	DR '08-9-10	mm	9201シリーズ ピンヘッダー SERIES 9201 PIN HEADER
△						① BASE : GLASS FILLED PBT UL94V-0 COLOR:BLACK	ANGLE 角度 ±	Y. Takeuchi	DSN '96-7-12	EDP No
△						② 端子/PIN : 銅/BRASS		M. MATSUDA	Matsu	PARTS No 部番
△						FINISH 仕上げ	3RD. ANG. PROJ. 三角法	CHK '08-9-10	APP '08-9-11	9201B-1-**Z248-PT1
△						① 磨めつき/PRE-PLATED		Y. Takeuchi	Y. Jaseki	DWG No 図番
△						② ニッケル下地めつき/OVER NICKEL PLATE 1.0μmMIN. ③ スズ/鉛めつき/TIN REFLOW PLATE 2.0μmMIN.		IRISO ELECTRONICS CO., LTD. IRISO 電子工業株式会社		REVISION 記
LTR 記号	ECN NO	REVISION RECORD 記	DR	CHK	DATE 年月日					IRISA-9201B-1-**Z248-PT1
08161		RELEASED	Y.T	M.T	'08-9-10					REV. 0