


極数 CKT	部品番号 PARTS No.	A	B	極数 CKT	部品番号 PARTS No.	A	B
2	9210B-1-02Z058-PT1	2.0	3.9	18	9210B-1-18Z058-PT1	34.0	35.9
3	9210B-1-03Z058-PT1	4.0	5.9	19	9210B-1-19Z058-PT1	36.0	37.9
4	9210B-1-04Z058-PT1	6.0	7.9	20	9210B-1-20Z058-PT1	38.0	39.9
5	9210B-1-05Z058-PT1	8.0	9.9	21	9210B-1-21Z058-PT1	40.0	41.9
6	9210B-1-06Z058-PT1	10.0	11.9	22	9210B-1-22Z058-PT1	42.0	43.9
7	9210B-1-07Z058-PT1	12.0	13.9	23	9210B-1-23Z058-PT1	44.0	45.9
8	9210B-1-08Z058-PT1	14.0	15.9	24	9210B-1-24Z058-PT1	46.0	47.9
9	9210B-1-09Z058-PT1	16.0	17.9	25	9210B-1-25Z058-PT1	48.0	49.9
10	9210B-1-10Z058-PT1	18.0	19.9	26	9210B-1-26Z058-PT1	50.0	51.9
11	9210B-1-11Z058-PT1	20.0	21.9	27	9210B-1-27Z058-PT1	52.0	53.9
12	9210B-1-12Z058-PT1	22.0	23.9	28	9210B-1-28Z058-PT1	54.0	55.9
13	9210B-1-13Z058-PT1	24.0	25.9	29	9210B-1-29Z058-PT1	56.0	57.9
14	9210B-1-14Z058-PT1	26.0	27.9	30	9210B-1-30Z058-PT1	58.0	59.9
15	9210B-1-15Z058-PT1	28.0	29.9	31	9210B-1-31Z058-PT1	60.0	61.9
16	9210B-1-16Z058-PT1	30.0	31.9	32	9210B-1-32Z058-PT1	62.0	63.9
17	9210B-1-17Z058-PT1	32.0	33.9				

仕様

- 1. 最大定格電圧電流 : 250V, 3A (AC, DC)
- 2. 使用温度範囲 : -40 ~ +105°C

NOTE

- 1. MAXIMUM RATING VOLTAGE AND CURRENT : 250V, 3A (AC, DC)
- 2. TEMPERATURE RANGE : -40 ~ +105°C



△					MATERIAL 材質	GENERAL TOLERANCES 一般公差	SCALE 尺度	UNIT 単位	TITLE 名称
△					①ベース: ガラス入 UPA66, UL94V-0, 灰色 BASE: GLASS FILLED PA66, UL94V-0, COLOR: GRAY	DIM 寸法 ± 0.3	DR '08-6-26 S. Kasai	MM	7210シリーズ ピンヘッダー SERIES 9210 PIN HEADER
△					②端子/PIN: 黄銅/BRASS	ANGLE 角度 ±	CHK '08-6-26 M. TAKASHI	DSN '88-7-16 Takahashi	EDP No
△					FINISH 仕上げ	3RD. ANG. PROJ. 三角法	APP '08-6-26 G. Sasaki	PARTS No 部番	9210B-1-**Z058-PT1
△					②前めっき/PRE-PLATE ニッケル下地めっき/OVER NICKEL PLATE 1μmMIN. 錫リフローめっき/TIN REFLOW PLATE 2μmMIN.		IRISO ELECTRONICS CO., LTD イリソ電子工業株式会社	DWG No 図番	IMS-9210B-1-**Z058-PT1
△	329/	Revised	S.K	MT	6/26 '08			REV.	3
△	記号	REVISION RECORD 記	DR	CHK	DATE 年月日				

DO NOT SCALE DRAWING. THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO IRISO AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.