



極数	部品番号	A	B
CKT	PARTS No.		
2	9210B-1-02Z694-PT1	2.0	3.9
4	9210B-1-04Z694-PT1	6.0	7.9
5	9210B-1-05Z694-PT1	8.0	9.9
6	9210B-1-06Z694-PT1	10.0	11.9
7	9210B-1-07Z694-PT1	12.0	13.9
8	9210B-1-08Z694-PT1	14.0	15.9
20	9210B-1-20Z694-PT1	38.0	39.9

△5  
△6

仕様

- 1. 最大定格電圧電流 : 250V, 3A (AC, DC)
- 2. 使用温度範囲 : -40~+105℃

NOTE

- 1. MAXMUM RATING VOLTAGE AND CURRENT : 250V, 3A (AC, DC)
- 2. TEMPERATURE RANGE : -40~+105℃

ISSUED  
'14.7.-2  
IRISO  
ENG. DEPT

△						MATERIAL 材質	GENERAL TOLERANCES 一般公差	SCALE 尺度	UNIT 単位	TITLE 名称
△						①ハース: ガラス入りPA46, UL94V-0, 自然色(アイボリー) BASE: GLASS FILLED PA46, UL94V-0, COLOR: NATURAL (IVORY) ②端子/ピン: 黄銅/BRASS	DIM 寸法 ± 0.3 ANGLE 角度 ±	DR '14-6-27 M. Tajima	mm	9210シリーズ ピンヘッダー SERIES 9210 PIN HEADER
△						FINISH 仕上げ	3RD. ANG. PROJ. 三角法	CHK '14.6.30 M. Takahashi	DSN '03-12-15 Y. Nakahashi	EDP No
△	48070	NOTE REV	M. T	M. T	'14-6-27	②前めっき/PRE-PLATE ニッケル下地めっき/OVER NICKEL PLATE 1μmMIN. 錫リフローめっき/TIN REFLOW PLATE 2μmMIN.		APP '14.6.30 M. Tajima		PARTS No 部番 1MSA-9210B-1-**Z694-PT1
△	47404	NOTE REV	L. Q	T. Ura	'14-4-1					DWG No 図番 110-209210-009
△	33452	REVISED	T. H	M. T	'08-10-28					REV. 6
△	記号	REVISION RECORD	DR	CHK	DATE					

DO NOT SCALE DRAWING. THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO IRISO AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. 本図面は、イリソ電子工業(株)の所有する情報を含むもので当社の許可なく複製を禁止する。

REDUCED COPY