


極数	部品番号	A	B	極数	部品番号	A	B
CKT	PARTS No.			CKT	PARTS No.		
2	9210B-1-02ZA225-PT1	2.0	3.9	18	9210B-1-18ZA225-PT1	34.0	35.9
3	9210B-1-03ZA225-PT1	4.0	5.9	19	9210B-1-19ZA225-PT1	36.0	37.9
4	9210B-1-04ZA225-PT1	6.0	7.9	20	9210B-1-20ZA225-PT1	38.0	39.9
5	9210B-1-05ZA225-PT1	8.0	9.9	21	9210B-1-21ZA225-PT1	40.0	41.9
6	9210B-1-06ZA225-PT1	10.0	11.9	22	9210B-1-22ZA225-PT1	42.0	43.9
7	9210B-1-07ZA225-PT1	12.0	13.9	23	9210B-1-23ZA225-PT1	44.0	45.9
8	9210B-1-08ZA225-PT1	14.0	15.9	24	9210B-1-24ZA225-PT1	46.0	47.9
9	9210B-1-09ZA225-PT1	16.0	17.9	25	9210B-1-25ZA225-PT1	48.0	49.9
10	9210B-1-10ZA225-PT1	18.0	19.9	26	9210B-1-26ZA225-PT1	50.0	51.9
11	9210B-1-11ZA225-PT1	20.0	21.9	27	9210B-1-27ZA225-PT1	52.0	53.9
12	9210B-1-12ZA225-PT1	22.0	23.9	28	9210B-1-28ZA225-PT1	54.0	55.9
13	9210B-1-13ZA225-PT1	24.0	25.9	29	9210B-1-29ZA225-PT1	56.0	57.9
14	9210B-1-14ZA225-PT1	26.0	27.9	30	9210B-1-30ZA225-PT1	58.0	59.9
15	9210B-1-15ZA225-PT1	28.0	29.9	31	9210B-1-31ZA225-PT1	60.0	61.9
16	9210B-1-16ZA225-PT1	30.0	31.9	32	9210B-1-32ZA225-PT1	62.0	63.9
17	9210B-1-17ZA225-PT1	32.0	33.9				

仕様

- 1. 最大定格電圧電流 : 250V, 3A(AC,DC)
- 2. 使用温度範囲 : -40~+105°C

NOTE

- 1. MAXIMUM RATING VOLTAGE AND CURRENT : 250V,3A
- 2. TEMPERATURE RANGE : -40°C TO +105°C



△						MATERIAL 材質	GENERAL TOLERANCES 一般公差	SCALE 尺度	UNIT 単位	TITLE 名称
△						① ベース : ガラス入り46ナイロン樹脂, UL94V-0 自然色(アイボリー)	DIM 寸法 ± 0.3	DR '07-12-11	mm	9210シリーズ ピンヘッダー SERIES 9210 PIN HEADER
△						BASE : GLASS FILLED 46NYLON, UL94V-0 COLOR:NATURAL(IVORY)	ANGLE 角度 ±	S Kasai	DSN '06-10-1	EDP No
△						② 端子/PIN : 黄銅/BRASS		CHK '07-12-11	Kasai	PARTS No 部番
△						FINISH 仕上げ	3RD. ANG. PROJ. 三角法	APP '07-12-11	Y. Sasaki	9210B-1-**-ZA225-PT1
△	3/10/02	REVISED	S-F	17.7	12/25/07	前めつき/PRE-PLATED		IRISO ELECTRONICS CO., LTD		DWG No 図番
△	3/20/04	RELEASED	S-F	10.4	12/11/07	ニッケル下地めつき/OVER NICKEL PLATE : 1µmMIN. 錫リフロー/TIN-REFLOW PLATE : 2µmMIN.		IRISO 電子工業株式会社		IMSA-9210B-1-**-ZA225-PT1
LTR 記号	ECN No	REVISION RECORD 記	DR	CHK	DATE 年月日					REV. 1