

極数/KCT	部品番号/PARTS No.	A	B	C	D	E	F
6	9890S-06Y80*	11.5	14.2	28.4	32	26	2±0.1
8	9890S-08Y80*	14.0	20.2	40.4	44	37	2±0.15
10	9890S-10Y80*	16.5					
12	9890S-12Y80*	19.0					
14	9890S-14Y80*	21.5					
16	9890S-16Y80*	24.0	26.2	52.4	56	49	
18	9890S-18Y80*	26.5					
20	9890S-20Y80*	29.0					
22	9890S-22Y80*	31.5					
24	9890S-24Y80*	34.0					
26	9890S-26Y80*	36.5					
28	9890S-28Y80*	39.0	34.2	68.4	72	65	
30	9890S-30Y80*	41.5					

梱包番号/PACKING No.	製品番号/PARTS No.	ボス/BOSS	カプトンテープ/TAPE
9890S-**Y807	9890S-**Z33-GT2	WITHOUT	WITH
9890S-**Y808	9890S-**Z34-GT2	WITH	WITH

NOTE  
1. 梱包数量 / UNIT QUANTITY : 700  
2. リードテープ長さ / LEAD TAPE LENGTH


製品引き出し方向  
PRODUCT WITHDRAWAL DIRECTION

カバートープリーダー部  
COVER TAPE STARTING

160Min.  
100Min.  
製品挿入部  
PRODUCT FILLING PORTION  
リーダー部/STARTING

3. カバートープの剥離強度 / COVER TAPE PEELING FORCE : 0.2~1.3N  
製品引き出し方向  
PRODUCT WITHDRAWAL DIRECTION

4. 10ピッチの累積許容は±0.2mmとする。  
THE TOTAL TOLERANCE OF 10 PITCH IS ±0.2.  
5. 適用極数/APPLY TO: 10~30PIN



MATERIAL 材質		GENERAL TOLERANCES 一般公差		SCALE 尺度	UNIT 単位	TITLE 名称
①カバートープ/COVER TAPE : PET TYPE ②キャリアテープ/CARRIER TAPE : PS ③リール/REEL : PS (黒/BLACK)		DIN 寸法 ± 0.3 ANGLE 角度 ±		DR 18-3-5 J. Nakayama	DSN 95-11-18 Suzuki	9890シリーズ ソケット エンボス梱包品 SERIES 9890 SOCKET EMBOSS PRODUCT
FINISH 仕上げ		3RD. ANG. PROJ. 三角法		CHK 18.3.5 M. Takahashi	APP 18-3-5 G. Uemura	EDP No
		IRISO ELECTRONICS CO., LTD イリソ電子工業株式会社				PARTS No 部番 MSA-9890S-**Y (807, 808)
5439/ RELEASED T.N M.T 18-3-5		3RD. ANG. PROJ. 三角法				DWG No 図番 120-409890-461
DO NOT SCALE DRAWING. THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO IRISO AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	REVISION RECORD	DR	CHK	DATE	REV.	0

DO NOT SCALE DRAWING.  
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO IRISO AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. 本図面は、イリソ電子工業(株)の所有する情報を含むもので当社の許可なく複製を禁止する。